

ELINK 61850 COMMUNICATION SOLUTION



**IEC 61850 network
communication gateway
for TRIAD 2 transducers
and ENERIUM power
monitors**



Communication:
IEC 61850 - Edition 2 server
Modbus RS485 Master

TRIAD 2 and ENERIUM seen as IEC 61850 native products

Easy implementation via web pages

High performance: up to 20 slave devices

The ELINK 61850 communication gateway

can be used to connect ENERIUM power monitors and TRIAD 2 transducers to an IEC 61850 network. The ENERIUM and TRIAD 2 products are seen as IEC 61850 native products by any supervision system or IEC 61850 SCADA / RTU client PLC.

1

Neutral

ELINK 61850 can be used to provide IEC 61850 communication without calling into question your choice or your qualification of an Enerdis measurement solution.

2

Installation upgrade

ELINK 61850 interfaces with the equipment already in place, enabling you to modernize your installation into an IEC 61850 digital substation.

3

Comprehensive

All the electrical measurements from the Enerdis measuring equipment are handled by the IEC 61850 communication protocol:

- Instantaneous measurements for TRIAD 2
- Instantaneous, min/max/average, energy and energy quality measurements for ENERIUM

4

Upgradable

The teams at Enerdis respond quickly to propose solutions for adapting ELINK 61850 to your application

To order

ELINK 61850

P01380850

Electrical specifications

Auxiliary power supply	AC: 80 to 265 Vac - 10 VA / 42.5 to 69 Hz DC: 80 to 265 Vdc - 7 W
Power reserve	2.5 seconds (with 230 Vac)

Communication - IEC 61850 protocol

Sections	IEC 61850-1, IEC 61850-5, IEC 61850-7
Logical nodes supported	MMXU, MMXN, MSTA, MMTR (Triad2/Enerium) MHAI, MHAN (Enerium)
Ethernet port	RJ45 - 8 contacts / 10 - 100 baseT
RS485A and RS485B ports	Type: independent RS485 - 2 isolated wires Protocol: Modbus RTU mode Operation: Master / Half-duplex mode Speed: 300 to 115,200 bauds

Mechanical specifications

Weight	560 g
Mounting	On DIN rail
Connection	Screw terminal block
Cable cross-sections	6 mm ² single wire - 4 mm ² multi-wire
Dimensions	120.5 x 120 x 81 mm (WxLxH)

Environmental constraints

Operating temperature	-10 °C to +55 °C
Storage temperature	-25 °C to +70 °C
Ingress protection	IP20
Pollution degree	2
Installation category	III
Safety standard	IEC 61010
Electromagnetic standards	IEC 61000-4-2/3/4/5/6/8/11/12/18 - CISPR22 IEC 61000-6-5 (Zone 2 - Station standard)

Enerdis measurement solutions



ENERIUM 50 / 150



ENERIUM 100 / 200 / 300



TRIAD 2

Network architecture



FRANCE
Chauvin Arnoux
190, rue Championnet
75876 PARIS Cedex 18
Tél : +33 1 44 85 44 85
Fax : +33 1 46 27 73 89
info@chauvin-arnoux.fr
www.chauvin-arnoux.fr

UNITED KINGDOM
Chauvin Arnoux LTD
Unit 1 Nelson Ct, Flagship Sq, Shaw Cross Business Pk
Dewsbury, West Yorkshire - WF12 7TH
Tel: +44 1924 460 494
Fax: +44 1924 455 328
info@chauvin-arnoux.co.uk
www.chauvin-arnoux.com

MIDDLE EAST
Chauvin Arnoux Middle East
P.O. BOX 60-154
1241 2020 JAL EL DIB - LEBANON
Tel: +961 1 890 425
Fax: +961 1 890 424
camie@chauvin-arnoux.com
www.chauvin-arnoux.com

**CHAUVIN
ARNOUX**
GROUP